


*Capture a Complete Spectrum of Functionality for Research,  
Medical Education and Training, and Consultation*



- **OLYMPUS CORPORATION** is ISO14001 certified.
- **OLYMPUS CORPORATION** is FM553994/ISO9001 certified.
- **Illumination devices for microscope** have suggested lifetimes. **Periodic inspections are required. Please visit our website for details.**
- This product is designed for use in industrial environments for the EMC performance. Using it in a residential environment may affect other equipment in the environment.
- All company and product names are registered trademarks and/or trademarks of their respective owners.
- Images on the PC monitors are simulated.
- Specifications and appearances are subject to change without any notice or obligation on the part of the manufacturer.

Art. code: E0438711 - 02/2014








# AN IDEAL CHOICE FOR STATE-OF-THE-ART RESEARCH FACILITIES AND DIGITAL LEARNING PROGRAMS

## Enhanced Research Tool for Brightfield and Fluorescence

The VS120 not only creates high resolution brightfield images, but also can scan in full multi-fluorescence mode. Utilizing virtual microscopy for fluorescence imaging helps to minimize problems associated with damaging and fading of sensitive fluorescence samples. An innovative new algorithm makes image stitching more precise than ever — enabling high-level accuracy that can be applied from small animal brain slices to large specimens. The VS120 also switches seamlessly between micro and macro observation to enable swift viewing of regions of interest and overall structures alike.



## A d v a n c e d V i r t u a l S l i d e S y s t e m



Brightfield/Fluorescence Observation Configuration  
(With 100-slide Storage Capacity)


The islet of insulin-deficient diabetic mouse, DAPI (blue), insulin (red)

Image data courtesy of  
Daisuke Sakano, Ph.D., Shoen Kume, Ph.D.  
Department of Stem Cell Biology, Institute of Molecular Embryology and Genetics, Kumamoto University




## Advanced Medical Education and Collaboration

The VS120 allows multiple viewers to study virtual slide specimens simultaneously via simple server access, regardless of time and location — providing an ideal solution for medical instruction, Q&A session and remote collaboration.



## Remote Conferencing and Consultation

Virtual slides can be archived to a database, enabling network-based remote retrieval at any time through the Olympus NISSQL NetImage Server. Images are stored at high resolution, and multiple clients can review and even synchronize elements such as specific observation areas to facilitate efficient review and discussion.





## HIGH-DETAIL, HIGH-PRECISION, RAPID SCANNING

### Wide Range of Objectives from 2x to 40x\*


The VS120 comes standard with Olympus UPLSAPO 2x, 10x, 20x and 40x objectives, allowing the user to choose an objective most suitable for his or her research needs. Automatic specimen recognition capability limits scanning to the specimen area, with high-level color fidelity and image quality.

*\*Other objectives may be used, but Olympus does not guarantee the performance of these objectives. Customers are highly encouraged to test the performance of non-standard objectives with their own specimens prior to purchase.*




### Virtual-Z with 3D Virtual Slide Production

The VS120 can scan multiple large specimens through up to 31 Z-planes. Multi-plane virtual slides can then be produced by simply selecting attributes such as depth for multiple areas, range, number of planes, and magnification within the virtual-Z scan mode. Virtual-Z scanning also allows the user to adjust the image to the specific desired depth with the simple scroll of a mouse — a function particularly advantageous for the viewing of thicker specimens, such as cell clusters or cranial nerves.



### Accurate Image Stitching, Regardless of Specimen Quality


A newly developed algorithm makes image stitching with the VS120 so precise, it can even capture quality composite images across large and uneven specimen regions.



VS120 minimizes stitching errors by automatically recognizing only where specimen exists then integrating images of consecutive areas.

### Supporting High-Resolution, High-Sensitivity Virtual Fluorescent Slides

High-speed filter wheels of the fluorescent unit can be installed on both the excitation and observation side, enabling the swift production of fluorescent virtual slides with high-level definition and resolution. Multi-colored virtual slides also can be prepared for long-term observation, negating concerns over fading, discoloration, and degradation.




### Automation Enhances Laboratory Efficiency

An optional automated slide loader with a capacity to hold 100 slides adds efficiency to laboratories with high throughput requirements. Furthermore, specimen information can be automatically read using 1D and 2D barcode scanner, making it easier to store and organize information.

## FUNCTIONALITY TO SERVE A RANGE OF OBSERVATION NEEDS


### Select the Desired Scanning Area Without the Need to Adjust Settings

Because the VS120 displays the scan area and focus mapping settings on the same screen, the desired scan area can be selected in an instant — bringing greater efficiency to your overall workflow by doing away with the need to switch screens.



### View Full and Magnified Images on the Same Screen

Both the whole slide and zoomed-in region can be displayed on the same screen, making it easy to pinpoint the specific location on the larger image.




EGFP-electroporated chick embryos  
DAPI (blue), EGFP (green), Islet1/2 (red), laminin (Cyan)

Image data courtesy of:  
Hiroshi Yajima, Ph.D., Kiyoshi Kawakami, Ph.D.  
Division of Biology, Center for Molecular Medicine,  
Jichi Medical University


### An Innovative Synchronizing Feature Enables Comparative Viewing of the Same Sample Under Different Stains

Analysis of the multiple virtual slides prepared from the same specimen is made easy through the ability to align them on the monitor with positions and magnifications interlinked.



### Save Annotation Voice Data

An innovative annotation function allows the user to save and link text and voice data to specific regions of interest on the slide.



A DATABASE PROVIDING SIMPLE OPERATION (OPTION)


Powerful and Fast Search Functionality

Virtual slides are easily found by using keywords through the folder tree. Simply double-clicking on the corresponding thumbnail image opens the desired virtual slide in a new window.

Attach Metadata to Virtual Slides

The VS120 provides editable metadata fields that can be used to store data such as tissue name, staining method, organ name, system, instructor's name and other keywords. Such information appended to slides, can assist greatly in an educational setting.

Example of a Virtual Slide Search



Batch Management of Digital Content

Offering functionality beyond virtual slides, the VS120 allows a wide range of image data to be archived to a database in both JPEG and TIFF formats, including macro images captured by other devices such as endoscopic images, X-ray images and electrocardiograms. Users are also able to save Microsoft Word, Excel and PowerPoint documents to the database.




Specifications

		VS120-S1	VS120-S5	VS120-L100
Intended Specimen	Observable Specimen	Glass slide with cover glass		
	Size of Glass Slide	Width: 25mm–26mm, length: 75mm–76mm, thickness: 0.8mm–1.4mm		
	Size of Cover Glass	Thickness: 0.12mm–0.17mm		
Microscope Frame	Illuminator	Built-in Koehler illumination for transmitted light		
	Objective Lenses	2x,10x, 20x, 40x with a motorized revolving nosepiece		
	Motorized Stage	Motorized XY stage with automatic control		
	Focusing	Motorized automatic control		
	Fluorescence Observation (Option)	Motorized fluorescence illuminator, Motorized filter wheel, Fluorescence light source, Digital monochrome camera		
Digital Camera	CCD Camera	2/3" CCD camera, 3.45μm x 3.45μm pixel size, high sensitivity, high resolution		
	Image Correction	Shading correction, auto white balance		
Scan	Capacity	1 slide (manual)	5 slides (maximum) (manual)	100 slides (maximum) (automatic)
	Scan Area	W 26mm x H 64 mm (Slide glass size: W26mm x H76mm)		
	Resolution	Less than 0.33μm/pixel when using 20x objective, less than 0.17μm/pixel when using 40x objective		
	Scan Time	Approx. 2 min. (20x objective lens, scan area 15mm x 15mm brightfield)		
System Control	OS	Compatible with Windows 7 Professional 64bit English version		
	Network Interface	100/1000Mbps Ethernet		
	Memory	8GB RAM (16GB RAM as Optional)		
	Hard Disc Drive	1.0TB or more		
	Display	24" TFT wide monitor		
Environment	Software	Image format: vsi, JPEG, TIFF/zooming while scanning/annotations/automatic sample detection/ Z stack extended focus imaging/screen capture/stepless zooming/synchronized multi-images display automatic stitching/slide loader control consultation software (option)		
	Weight	Approx. 52kg (incl. controller and display)		Approx. 100kg (incl. controller and display)
	Operating Environment	Temperature: 15–28 degree centigrade, humidity: 30%–80% (non condensing)		
	Power	Scanner: AC 100–120/220–240V, 50/60Hz, 3.5A/1.5A Controller: AC 100–120/200–240V, 50/60Hz, 10A/6A Display: AC 100–240V, 50/60Hz, 1.5A Slide loader: AC 100–120/220–240V, 50/60Hz, 0.9A/0.5A (VS120-L100 Only)		
	Power Consumption	960W	960W	1030W

Dimensions

(Unit: mm)

Fluorescence Observation Configuration (With 5-slide Storage Capacity)



Brightfield Observation Configuration (With 100-slide Storage Capacity)

